

ARMARIO GN 2-1

ARMARIO REFRIGERACIÓN GN-2/1 ARG-75 / GN-2/1 CABINET CHILLER



CARACTERÍSTICAS GENERALES



- Exterior en acero inox AISI-304 18/10, excepto el respaldo
- Costados en acero inox AISI-304 con 22 embuticiones para apoyo de parrillas y cubetas GN 1/1 o GN 2/1
- Puertas de apertura reversible, con sistema de cierre automático y burlete magnético (permanece abierta al superar los 90° de apertura)
- Contrapuerta inox embutida
- Luz interior
- Estantes interiores de varilla en acero plastificado, regulables en altura
- Pies en tubo de acero inox ajustables en altura 125-200 mm
- Cuadro de mandos y rejilla ventilación motor, desmontables
- Unidad condensadora ventilada
- Evaporador sistema tiro forzado, con recubrimiento anticorrosión
- Paro ventiladores tiro forzado al abrir la puerta
- Evaporación automática del agua de descarache
- Aislamiento de poliuretano inyectado, densidad 40 Kg/m³, bajo GWP y cero efecto ODP
- Control digital de temperatura, descárches optimizados, alarma por puerta abierta y alta temperatura de condensación. Eficiente gestión del consumo de energía
- Temperatura de trabajo a 32°C ambiente

GENERAL FEATURES

- AISI-304 18/10 stainless steel exterior, except the rear side
- Sides in stainless steel AISI-304 with 22 embossments to support shelves and trays GN 1/1 or GN 2/1
- Doors with self closing system, blocked opening, magnetic gasket and possibility of changing the opening sense
- Rear-door by stamped steel
- Interior lighting
- Shelves made of plasticized steel wire, height adjustable
- AISI-304 18/10 adjustable legs, 125 to 200 mm
- Control panel and engine ventilation grill, removable
- Fan assisted condenser unit
- Fan assisted evaporator, with anticorrosion coating
- Evaporator fan stops when door is opened
- Automatic evaporation of defrost water
- 40 Kg/m³ density polyurethane insulation, low GWP and zero ODP effect
- Digital temperature control, optimized defrosting, open door alarm and high condensing temperature. Efficient management of energy consumption
- Operating temperature 32°C ambient

*Características técnicas y constructivas sujetas a variación sin previo aviso, todas las fotos deben ser consideradas como una referencia
Technical and constructive characteristics subject to variation without prior notice, all photos must be considered as a reference*

ARMARIO GN 2-1

ARMARIO REFRIGERACIÓN GN-2/1 ARG-75 / GN-2/1 CABINET CHILLER

AGR / ACG

AGRE / ACGE

Modelo Model Modèle	Largo Length Longueur mm	Alto Height Hauteur mm	Fondo Depth Profondeur mm	Rango Range Gamme	Estantes Shelves Étagères GN 2/1	Capacidad Capacity Exposition	Voltaje Voltage Tension	Refrig. Coolant Frigorigène	Potencia Frig. Frig Power Puissance Frig. W	Consumo Nominal Nominal Consumption Consommation Nominale W	Rango Range Gamme	Rango Range Gamme
ARG-75	680	2130	850	-2°C +8°C	3	645	230 V - 50 Hz	R-290	502	243	C	5 (40°C 40%)
ARGV-75	680	2130	850	-2°C +8°C	4	645	230 V - 50 Hz	R-290	502	260	-	5 (40°C 40%)

Características técnicas y constructivas sujetas a variación sin previo aviso, todas las fotos deben ser consideradas como una referencia
 Technical and constructive characteristics subject to variation without prior notice, all photos must be considered as a reference