

# MESA FRÍA SNACK PRE-INSTALACION BMCP

MESA FRÍA SNACK MANTENIMIENTO CONGELADOS / SNACK COUNTER FREEZER



**BMCP**



**BMCP-V**

## CARACTERÍSTICAS GENERALES

- Exterior en acero inox AISI-304 18/10, excepto el respaldo
- Interior en acero inox AISI-304 18/10, con aristas curvas y fondo embutido
- Puertas de apertura reversible, con sistema de cierre automático
- y burlete magnético (permanece abierta al superar los 90° de apertura)
- Contrapuerta inox embutida
- Luz interior en modelos puerta de cristal
- Encimera de acero inox AISI-304 18/10 con frente curvo y peto trasero sanitario de 100 mm (opcional sin peto según modelo)
- Estantes interiores de varilla en acero plastificado, regulables en altura, sobre apoyos inox
- Pies en tubo de acero inox ajustables en altura 125 200 mm
- Evaporador sistema tiro forzado, con recubrimiento anticorrosión
- Evaporación automática del agua de descarche de serie, excepto modelos pre-instalacion
- Aislamiento de poliuretano inyectado, densidad 40 Kg/m<sup>3</sup>, bajo GWP y cero efecto ODP
- Control digital de temperatura y descarches, eficiente en la gestión del consumo de energía
- Temperatura de trabajo a 32°C ambiente
- Cajoneras inox refrigeradas desmontables sobre guías telescópicas con sistema autocierre


## GENERAL FEATURES

- AISI-304 18/10 stainless steel exterior, except the rear side
- AISI-304 18/10 stainless steel interior, stamped bottom and rounded corners
- Doors with self closing system, blocked opening, magnetic gasket and possibility of changing the opening sense
- Rear-door by stamped steel
- Interior light in glass door models
- AISI-304 18/10 stainless steel worktop, with round-ed front and 100 mm sanitary up stand (optional without up stand depending on model)
- Shelves made of plasticized steel wire, height adjustable by stainless steel supports
- AISI -304 18/10 adjustable legs, 125 to 200 mm
- Fan assisted evaporator, with anticorrosion coating.
- Automatic evaporation of defrost water as standard, except models preinstalation
- 40 Kg/m<sup>3</sup> density polyurethane insulation, low GWP and zero ODP effect
- Energy efficient digital controller of temperature and defrosts
- Operating temperature 32°C ambient
- Removable stainless refrigerated drawers on telescopic guides with self-closing system

*Características técnicas y constructivas sujetas a variación sin previo aviso, todas las fotos deben ser consideradas como una referencia  
Technical and constructive characteristics subject to variation without prior notice, all photos must be considered as a reference*

# MESA FRÍA SNACK PRE-INSTALACION BMCP

MESA FRÍA SNACK MANTENIMIENTO CONGELADOS / SNACK COUNTER FREEZER



Modelo	Largo	Alto	Fondo	Potencia Frig.	Capacidad	Peso Neto	Estantes x set	Voltaje	Refrig.	Rango
Model	Length	Height	Depth	Frig Power	Capacity	Net Weight	Shelves x set	Voltage	Coolant	Range
Modèle	Longueur	Hauteur	Profondeur	Puissance Frig.	Exposition	Poids Net	Étagères x set	Tension	Frigorigène	Gamme
BMCP/BMCPV-120	1195	850	600	353	245	68	2	230 V - 50 Hz	R-449A	-20°C-15°C
BMCP/BMCPV-170	1720	850	600	452	380	89	3	230 V - 50 Hz	R-449A	-20°C-15°C
BMCP/BMCPV-220	2245	850	600	610	516	110	4	230 V - 50 Hz	R-449A	-20°C-15°C

Características técnicas y constructivas sujetas a variación sin previo aviso, todas las fotos deben ser consideradas como una referencia  
Technical and constructive characteristics subject to variation without prior notice, all photos must be considered as a reference